














- Toshiba x-ray tube 140 HU 1-2mm focal spot
- kVp range: 40-150kV
- Single Phase 208-230VAC
- High frequency 32 kW capacitor assisted 400mA generator
- 15" Touch Screen Operator Console



- Low input amperage
- SMART APR
- Remote real-time monitoring, calibration and maintenance features (optional)
 - Exclusive self-diagnostic tool based on lot and machine learning
 - Eliminate need for onsite service technicians



- Six exclusive design table base/table top designs
 - 30" Base w/40", 48", 56" table top options
 - 40" base w/48", 56", 64" table top options
 - Oval top w/urine track
- Unique Push and Open pull out tray to access DR detector
- Exclusive Push and Open Front panel latch mechanism for easy generator access



- Patented ATD (Auto Thickness Detection) technology
- Open APR integration: control kV, mA, and mS
- Exclusively control generator dosage (embedded AI/lot) by detecting body part for ideal exposure

🗷 🔰 Veterinary Specific Software 📠

ACQUISITION INTERFACE



. 3	Sedecal S. Say Petion (D.	
**************************************	Manager Company Compan	11 21
ne vis		20/20 Imaging
nities Part		TY
Presentation soft		
Technique		Archive Options
Cancel	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Exit

• Under 6 second () Processing

- Background Submission
- Preset X-ray Exams
- Animal Specific
- Annotomical Program (APR)
- Fully Customizable
- Advanced Image Processing
- Image Adjustment Tools
- Touchscreen Enabled
- User Friendly Interface







MOBILE VIEWING WITH M-OPAL





- Lightweight & Fast
- Patient List & Viewer
- Simple Annotations Enabled
- Tap, Drag, and Pinch
- Patient Filter & Search

17x17 UNIVERSAL DR FLAT PANEL



- Tethered Interface
- Cesium Scintillator
- 16-bit Images

- Cassete Sized
- 139 micron | 3.6 lp/mm
- 5 year MFG warranty



2020imaging.net/vetsmart

